



					Conditions: STATIC PRESSURE - Continuous Operation				HORSEPOWER	WEIGHT
220 VOLTS	208 VOLTS	440 VOLTS	480 VOLTS	575 VOLTS	MAXIMUM PRESSURE	MAXIMUM VACUUM	MAXIMUM AIRFLOW	MINIMUM AIRFLOW		
FLC-25.0 A	FLC-27.3 A	FLC-12.5 A	FLC-12.5 A	FLC-9.2A	135 in H2O	110 in H2O	388 SCFM	135 SCFM	10.0	718 lbs.

480 VOLT, 40 AMP CONNECTION IS PREFERRED. ** VERIFY POWER WITH ELECTRICIAN. ** (208 VOLT, 80 AMP) FLC = FULL LOAD CURRENT
 HOUSEKEEPING PAD IS OPTIONAL (BY OTHERS). THIS UNIT IS NOT DESIGNED TO BE HUNG. RECOMMENDED LOCATIONS IN A MECHANICAL AREA.
 A MINIMUM CLEARANCE OF 36" (THREE SIDES) & 18" (ON THE FOURTH SIDE) IS REQUIRED FOR MAINTENANCE & SERVICE ACCESS.
 Sound level is 82-84 dBA on 60 Hz unit. The unit vibration reading is less than 200 cycles per 1 minute. - Sound and vibration tests based on the module mounted directly on a concrete floor (without the housekeeping pad).



1401 Tangier Drive
 Baltimore, Maryland 21220
 T 410.931.8800, F 410.931.4660
 800.296.PEVCO (7382), www.pevco.com

**BLOWER MODULE
 w/ OPTIONAL HOUSEKEEPING PAD
 (Ethernet Communications)**

SCALE	NONE	DATE
DRAWN	SDW	01.28.13
REVISED	SDW	04.01.14
	-	-
DRAWING NUMBER	PEV225.2A	REVISION 1